

Product Line

Diesel 50Hz Range

We offer a complete line of mobile power products including generators from 2 – 19 kW. Mobile power is available in diesel, petrol and LP powered models.

Commercial Mobile Quiet Diesel Series (Remote radiator required)

Model		kW	Hz	Voltage	Amps	dB(A)*	Ph	Length x Width x Height in/mm	Weight lbs/kg
	QD7000	7	50	115/230	30.4	60	1	36/914 x 22/559 x 23/584	601/272
	QD9500	9.5	50	115/230	41.3	62	1	41/1041 x 22/559 x 23/584	695/315
	QD11000	11	50	115/230	47.8	62	1	41/1041 x 22/559 x 23/584	695/315
	QD13500	13.5	50	115/230	58.7	63	1/3	45/1143 x 24/610 x 28/711	892/404
	QD17500	17.5	50	115/230	76.1	63	1/3	45/1143 x 24/610 x 28/711	932/422
	QD19000	19	50	115/230	82.6	63	1/3	45/1143 x 24/610 x 28/711	932/422

Note: All above products come in 12V negative ground, single phase 230V configuration as standard. For 24V DC systems, 3 phase configurations and voltage options please refer to specification sheets or contact your nearest distributor/dealer.

* At 3m, before installation, full load.

Remote Radiator Specification

Generator Cooling Package		Size (in/mm)		
		L	H	W
	QD7000	17/430	14/368	20/508
	QD9500	20/520	16/410	22/570
	QD11000	20/520	16/410	22/570
	QD13500	23/595	16/410	27/682
	QD17500	23/595	16/410	27/682
	QD19000	23/595	16/410	27/682

Commercial Mobile Quiet Diesel Series

Model		kW	Hz	Voltage	Amps	dB(A)*	Ph	Length x Width x Height in/mm	Weight lbs/kg
	QD5000	4.8	50	230	21	68	1	34/876 x 23/581 x 20/515	400/181
	QD8000	8	50	230	35	66	1	41/1053 x 25/621 x 27/686	816/370

* At 3m, before installation, half load.

Commercial Mobile Standard Diesel Series

Model		kW	Hz	Voltage	Amps	dB(A)*	Ph	Length x Width x Height in/mm	Weight lbs/kg
	SD 6.0	6	50	115/230	52.1/26.1	75	1	37/942 x 21/533 x 24/610	491/223
	SD 6.0	6	50	Reconnectable			3	37/942 x 21/533 x 24/610	491/223
	SD 8.0	8	50	115/230	70/35	76	1	39/1003 x 21/533 x 26/662	519/236
	SD 8.0	8	50	Reconnectable			3	40/1028 x 21/533 x 26/662	519/236

* At 3m, before installation, full load.



Petrol & LP 50Hz Range

Commercial Mobile Quiet LP Series

Model		kW	Hz	Voltage	Amps	dB(A)*	Ph	Length x Width x Height in/mm	Weight lbs/kg
	QG2300 LP	2.3	50	230	10	70	1	22/559 x 16/417 x 13/330	125/57
	QG3300 LP	3.3	50	115/230	28.7/14.3	68	1	31/775 x 21/523 x 16/417	174/83

* At 3m, before installation, half load.

Commercial Mobile Quiet Petrol Series

Model		kW	Hz	Voltage	Amps	dB(A)*	Ph	Length x Width x Height in/mm	Weight lbs/kg
	QG2300 Petrol	2.3	50	230	10	70*	1	22/559 x 16/417 x 13/330	125/57
	QG3600 Petrol	3.6	50	115/230	31.3/15.7	68*	1	31/775 x 21/523 x 16/417	174/83
	QG5800 Petrol	5.8	50	230	25.2	68**	1	34/853 x 22/563 x 17/425	290/132

* At 3m, before installation, half load.
** At 3m, typical installation, full load.

Cummins Onan



Cummins Power Generation
Manston Park, Columbus Ave.
Manston, Ramsgate, Kent CT12 5BF
United Kingdom

Phone 44 1843 255000
Fax 44 1843 255902
Internet: power.cummins.com/cm

Cummins®, Onan® the 'C' logo, and Performance you rely on™ are trademarks or registered trademarks of Cummins Inc.
©2015 Cummins Power Generation. All Rights Reserved
EMERSB-6144-EN (9/15)

Performance you rely on.™

Specifications are subject to change without notice